EXCA233BNCx

innolech®
MANUFACTURERS OF INNOVATIVE SECURITY PRODUCTS

960H Indoor Dome Camera Recessed Mount

960H on lma n n ensor with over 730 TVL Resolution. Choose Day/Night, Color@Night® or WDR. Equiped with 2.8ð12 mm AIVF Lens, 12 VDC or Dual Voltage 12 VDC/24 VAC. Designed, engineered, assembled and tested in the USA.

SENSOR SELECTION

[illegible]	[illegible]	en or e
=sensor	C	960H, >730 TVL Day/Night
	H	[illegible] 79 Color@Night®
	P2	T WDR
VVV= o ta e	-12V	12 VD
	-DV	Dual Voltage 12 VDC / 2 V C

7HHHHHHHHHHPH

H79 21H5 HHP
HHHH

H7921H1HH
HHPHHHH5

2 960H WDR - 2nd generation e ulti ate WDR te nolog lu great lo lig t en itivit or nig t o eration

SPECIFICATIONS

Specs.	Type "C" Day/Night	Type "H" Color@Night®	Type " " WDR
Sensor	1/3" SONY	1/3" SONY	6R
Resolution	TVL NTSC	TVL NTSC	79/176
Min. Illumination	0.02 Lux	0.00002 Lux (Sense-Up x256)	u Color / 2 u W
Color@Night	N/A	YES	YES
S/N ratio (S/N)	52 dB (AGC off)	52dB	>G
White balance	ATW1, ATW2, MDnual	ATW1, ATW2, AWC, Manual	73XV8VHUWL53XV7RN0DXDO
Shutter	1/60–1/100,000	1/60–1/100,000	
Privacy Mask	8 Programmable Zones	8 Programmable Zones	1Programmable Zones
WDR	Digital Wide Dynamic Range (D - WDR)	N/A	WDOGHDPL5DH
DNR	2D DNR	3D DNR	3D Motion DNR
Mirror	Reverse (H)	Reverse (H/V)	Reverse (H/V)
Motion Detection	YES	YES	YES
Digital Zoom	N/A	X1 – X10 (x0.1 Steps)	X1 – X
OSD	YES	YES	YES
Power Supply	XDO9ROWDH12V DC / 24V AC	Dual Voltage 12VDC / 24VAC	XDO9ROWDH12V DC / 24V AC
Dimensions	4" x 2.5" x 2.2"	4" x 2.5" x 2.2"	4" x 2.5" x 2.2"

innolech®
1 00 We t Co an Road te -11
o ano ea 06
954-792-2818
HHHP
HHP