

Camera Selection

Innotech Camera	Type	Video	Sensor	Voltage (BNC Models)
EXCA	215 = Standard Body (no lens) 233 = Indoor Recessed Mount 234 = Outdoor Surface Mount, Vandal 235 = Indoor Surface Mount	CAT5 = SmartControl CAT5 BNC = Coax	C = 960H, >730TVL H = 960H, >730TVL, Color@Night P = Pixim Seawolf WDR, 690TVL SIR = 960H, 900TVL, 65ft. IR	-DV = Dual Voltage -12V = 12VDC Only -24V = 24VAC Only

Example: EXCA235BNCH-DV is an Innotech, Indoor Surface Mount, Coax, 960H Color@Night, Dual Voltage Camera. Domes include a 2.8 to 12mm lens.



215 Series



233 Series



234 Series



235 Series



EX100 - BNC to CAT5 Converter
12VDC/250mA cameras, (for use with CAT5 decoders)



AM26 - Pendant Cap
3/4" Threaded for
234/235 Series



EX400L-KIT



EX800L-KIT



EX1200L-KIT



EX1600L-KIT

Option: BNC_CAT5_CABLE – Allows standard coax & 12VDC/24VAC power for CAT5 version dome cameras
Option: Wired OSD Remote for Kits – EXCO200



AM7V2-KIT -
Wall Mount with Back
Box for 234/235 Series